


acniti LLC 1-2-9 Nyoidani Minoh Osaka 562-0011 Japan


Geniti

ozone destructor

The acniti ozone decomposer uses a catalytic method to remove excess ozone. The ozone destructor uses a modular optional approach with a Water trap, Heated chamber, Catalyst Sieve ozone destructor and Vacuum pomp. The modular approach makes ozone destruction possible many environmental conditions.







ozone destructor

ozone destructor breaks down ozone in ambient air

- Modular ozone decomposer
- Catalytic approach with Manganese Palladium oxide
- < Minimal maintenance ozone decomposer
- Many sizes possible, contact for requirements

ozone decomposition

Ozone is an enormously powerful molecule, useful for applications both in air and water treatment. After the ozone treatment process, residual high concentrations of ozone may still be present. When unwanted, this requires ozone destruction. Acniti developed a modular ozone destruction solution based on a catalysator which is scalable for small to large applications.

In research applications producing ozone off gas a small ozone decomposer will be sufficient. For large ozone contact tanks where it is not practical to release ozone into the atmosphere or reintroduce it in the water require a larger ozone destructor.


The acniti ozone decomposer uses a catalytic method to remove excess ozone. The catalyst is a transitional metal manganese dioxide in combination with palladium. The benefit of using a catalyst is that ozone does not consume the catalyst. Ozone destruction or decomposing takes place in a catalyst sieve where ozone converts into pure oxygen by the catalyst.

modular ozone destruction

To put ozone destruction into practice acniti has developed a modular system consisting of four steps. Step 3 is the core step of ozone destruction. The design of the other three steps is to protect equipment and the catalyst. These additional steps are optional depending on the destruction application:

Acniti modular ozone decomposer:

- Water trap
- Heated chamber
- Catalyst Sieve ozone destructor
- Vacuum pomp



×

the water-trap


Using the ozone destructor application with the risk of water entering the system, acniti recommends the water trap. In the event water is entering the system, the water trap will drain the water and protect the catalyst sieve en vacuum pump from getting wet.

heated chamber

When the humidity of the gas is higher than 75% acniti recommends a heater chamber, humidity higher than 85% requires the heater chamber. When the catalyst saturates with moisture it is no longer effectively breaking down ozone and requires regeneration or replacement. The heater has two effects on the ozone destruction process. The first is that warm air can hold more moisture and avoids the catalyst get moisture saturated. The second effect is that the warmer the air the less stable the ozone molecule is and the easier it breaks down to oxygen.

catalyst sieve

The core component of the ozone destruction system. Converts the ozone to oxygen.



ναςυυπ ροπρ

When there is no positive pressure on the inlet of the catalyst sieve. The ozone air mixture cannot move through the sieve as it requires force. The vacuum pump can suck the ozone air mixture through the sieve equipped with flow controller and flow indicator. So, it is easy to control the flow.

ozone destructor 101pm

	Description	Metric	Imperial
1	Model name	Ozone Destructor 10LPM	Ozone Destructor 10LPM
2	Model number	OD-10LPM-SUS-fittings	OD-10LPM-SUS-fittings

ozone destructor 251pm

	Description	Metric	Imperial
1	Model name	Ozone Destructor 25LPM	Ozone Destructor 25LPM
2	Model number	OD-25LPM-SUS-fittings	OD-25LPM-SUS-fittings



suction pump o3 decomposer 10 or 251pm

	Description	Metric	Imperial
1	Model name	suction pump O3 decomposer 10 or 25LPM	suction pump O3 decomposer 10 or 25LPM
2	Model number	tool_suction_pump_o3_d ecomposer_10_25lpm	tool_suction_pump_o3_deco mposer_10_25lpm