



**acniti LLC**  
1-2-9 Nyoidani  
Minoh Osaka  
562-0011  
Japan



## turbiti wall mount

The wall mounted Turbiti is the multipurpose nanobubble generator suitable for agriculture, horticulture and fish cultivation sites. Super saturation of oxygen for water day storage tanks in horticulture. Drinking water solutions for chicken, cows, pigs and horses, giving high DO water with ultrafine bubbles to animals with enhance their food digestion more efficiently and results in healthier animals.

## turbiti wall mount


### turbiti wall mounted nanobubble mixer with enhanced aeration technology

- ✓ Clean Tech – Chemical free cleaning solutions
- ✓ easy to implement in existing installations
- ✓ efficient gas dissolution and ultrafine bubble production
- ✓ uses turbiti nanobubble production technology
- ✓ systems in use for poultry and livestock drinking water
- ✓ nanobubble production for irrigation ponds for agriculture
- ✓ combined in wastewater treatment systems
- ✓ special chemical and hydrochloric acid resistant version available

The Turbiti O2 is the multipurpose ultrafine bubble generator suitable for agriculture, horticulture and fish cultivation sites. The Turbiti O2 must be combined with an oxygen generator, which creates 90% pure oxygen out of air.

Inside the turbiti O2 is Acniti's low pressure static mixer swirl flow technology, which creates billions of nano-sized bubbles by beating up the gas water mixture. The Turbiti O2 is flexible to implement, as it can be used with a wide array of pumps.

The turbiti O2 is used for aerating fishponds with nanobubbles. Super saturation of oxygen for water day storage tanks in horticulture. Drinking water solutions for chicken, cows, pigs and horses, giving high DO water with ultrafine bubbles to animals with enhance their food digestion more efficiently and results in healthier animals.



## turbiti 727 o2 nanobubble mixer in wall mounted enclosure specs

	Description	Metric	Imperial
1	Model name	Turbiti 727 O2 in wall mounted enclosure	Turbiti 727 O2 in wall mounted enclosure
2	Model number	turbiti_727_wallmount_galvanized-box	turbiti_727_wallmount_galvanized-box
	Liquid	Metric	Imperial
3	Minimum flow / minute	50 Liter	13 Gallon
4	Maximum flow / minute	100 Liter	26 Gallon
5	Minimum flow / hour	3.0 M3	105.9 CF
6	Maximum flow / hour	6.0 M3	211.9 CF
7	water temperature minimum	-20 °C	-4 °F
8	water temperature maximum	50 °C	122 °F
9	Strainer availability and size	No strainer on the equipment, strainer required when particles larger than 1 or 2 mm.	No strainer on the equipment, strainer required when particles larger than 1 or 2 mm.
10	Recommended inlet filter(s)	Medium pump inlet filter series	Medium pump inlet filter series
	Ambient	Metric	Imperial
11	Ambient temperature minimum	-20 °C	-4 °F
12	Ambient temperature maximum	50 °C	122 °F
13	Relative humidity minimum	0 %	0 %
14	Relative humidity maximum	100 %	100 %


	Gas	Metric	Imperial
15	Minimum flow / minute	2.5 Liter	0.7 Gallon
16	Maximum flow / minute	5.0 Liter	1.3 Gallon
17	Minimum flow / hour	150 Liter	40 Gallon
18	Maximum flow / hour	300 Liter	79 Gallon
19	Pressure minimum	50 kPa	7 PSI
20	Pressure maximum	350 kPa	51 PSI
21	Gas quality	No corrosive gasses: suitable for O2, air, CO2, N2	No corrosive gasses: suitable for O2, air, CO2, N2

22	Gas remark	The mentioned pressures are recommended pressures for bubble generation. The product itself can withstand pressures up to 500 kPa.	The mentioned pressures are recommended pressures for bubble generation. The product itself can withstand pressures up to 500 kPa.
----	------------	------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------

	Electrical	Metric	Imperial
23	Unit power consumption	No pump included with this product. Estimated power consumption 750-1000 watts.	No pump included with this product. Estimated power consumption 750-1000 watts.
24	Wetted parts	nylon based resins, PVC, EPDM rubber	nylon based resins, PVC, EPDM rubber
25	Pump model	Recommended: use of a low head centrifugal pump or pool pump	Recommended: use of a low head centrifugal pump or pool pump
26	Pump pressure setting	This product works well with most low head pumps. Head 10 to 15 meters. (Ask us for more details).	This product works well with most low head pumps. Head 10 to 15 meters. (Ask us for more details).
27	Control	Manual by pressure gauche	Manual by pressure gauche

### Pump

28	@option	Ebara-Matrix-5-3
----	---------	------------------

Connections		Metric	Imperial
29	Water inlet	Rigid Rc 1" female coupling with thread	Rigid Rc 1" female coupling with thread
30	Water outlet	rigid Rc 3/4" female coupling with thread	rigid Rc 3/4" female coupling with thread
31	Gas inlet	10 mm standard quick fitting, 3/8 on request	10 mm standard quick fitting, 3/8 on request
Dimensions & weight		Metric	Imperial
32	Dim. (w) x (d) x (h)	644 x 200 x 1040 mm	25.4 x 7.9 x 40.9 inch
33	weight	26.5 Kg	58.4 lbs.
34	Shipping dim. (w)x(d)x(h)	67 x 37 x 107 cm	26 x 15 x 42 inch
35	Shipping weight	35 Kg	77 lbs.
Remarks			
36	Other remarks	 Easy to integrate with existing pool pumps	

## turbiti 737 o2 nanobubble mixer in wall mounted enclosure specs

	Description	Metric	Imperial
1	Model name	Turbiti 737 O2 in wall mounted enclosure	Turbiti 737 O2 in wall mounted enclosure
2	Model number	turbiti_737_wallmount_galvanized-box	turbiti_737_wallmount_galvanized-box
	Liquid	Metric	Imperial
3	Minimum flow / minute	100 Liter	26 Gallon
4	Maximum flow / minute	250 Liter	66 Gallon
5	Minimum flow / hour	6.0 M3	211.9 CF
6	Maximum flow / hour	15 M3	530 CF
7	water temperature minimum	-20 °C	-4 °F
8	water temperature maximum	50 °C	122 °F
9	Strainer availability and size	No strainer on the equipment, strainer required when particles larger than 1 or 2 mm.	No strainer on the equipment, strainer required when particles larger than 1 or 2 mm.
10	Recommended inlet filter(s)	Medium pump inlet filter series	Medium pump inlet filter series
	Ambient	Metric	Imperial
11	Ambient temperature minimum	-20 °C	-4 °F
12	Ambient temperature maximum	50 °C	122 °F
13	Relative humidity minimum	0 %	0 %
14	Relative humidity maximum	100 %	100 %


	Gas	Metric	Imperial
15	Minimum flow / minute	5.0 Liter	1.3 Gallon
16	Maximum flow / minute	8.0 Liter	2.1 Gallon
17	Minimum flow / hour	300 Liter	79 Gallon
18	Maximum flow / hour	480 Liter	127 Gallon
19	Pressure minimum	50 kPa	7 PSI
20	Pressure maximum	300 kPa	44 PSI
21	Gas quality	No corrosive gasses: suitable for O2, air, CO2, N2	No corrosive gasses: suitable for O2, air, CO2, N2

22	Gas remark	The mentioned pressures are recommended pressures for bubble generation. The product itself can withstand pressures up to 500 kPa.	The mentioned pressures are recommended pressures for bubble generation. The product itself can withstand pressures up to 500 kPa.
----	------------	------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------

	Electrical	Metric	Imperial
23	Unit power consumption	No pump included with this product. Estimated power consumption 750-1000 watts.	No pump included with this product. Estimated power consumption 750-1000 watts.
24	Wetted parts	nylon based resins, PVC, EPDM rubber	nylon based resins, PVC, EPDM rubber
25	Pump model	Recommended: use of a low head centrifugal pump or pool pump	Recommended: use of a low head centrifugal pump or pool pump
26	Pump pressure setting	This product works well with most low head pumps. Head 10 to 15 meters. (Ask us for more details).	This product works well with most low head pumps. Head 10 to 15 meters. (Ask us for more details).
27	Control	Manual by pressure gauche	Manual by pressure gauche

## Pump

28	@option	Grundfos CM10-1
----	---------	-----------------

Pump		
29	@option	Ebara pump DWO-400
Connections	Metric	Imperial
30 Water inlet	Rigid Rc 2" female coupling with thread	Rigid Rc 2" female coupling with thread
31 Water outlet	rigid Rc 1" female coupling with thread	rigid Rc 1" female coupling with thread
32 Gas inlet	10 mm standard quick fitting, 3/8 on request	10 mm standard quick fitting, 3/8 on request
Dimensions & weight	Metric	Imperial
33 Dim. (w) x (d) x (h)	644 x 200 x 1040 mm	25.4 x 7.9 x 40.9 inch
34 weight	26.5 Kg	58.4 lbs.
35 Shipping dim. (w)x(d)x(h)	67 x 37 x 107 cm	26 x 15 x 42 inch
36 Shipping weight	35 Kg	77 lbs.
Remarks		
37 Other remarks	 Easy to integrate with existing pool pumps	




## turbiti 747 o2 nanobubble mixer in wall mounted enclosure specs

Description		Metric	Imperial
1	Model name	Turbiti 747 O2 in wall mounted enclosure	Turbiti 747 O2 in wall mounted enclosure
2	Model number	turbiti_747_wallmount_galvanized-box	turbiti_747_wallmount_galvanized-box
Liquid		Metric	Imperial
3	Minimum flow / minute	400 Liter	106 Gallon
4	Maximum flow / minute	500 Liter	132 Gallon
5	Minimum flow / hour	24 M3	848 CF
6	Maximum flow / hour	30 M3	1,059 CF
7	water temperature minimum	-20 °C	-4 °F
8	water temperature maximum	50 °C	122 °F
9	Strainer availability and size	No strainer on the equipment, strainer required when particles larger than 1 or 2 mm.	No strainer on the equipment, strainer required when particles larger than 1 or 2 mm.
10	Recommended inlet filter(s)	Medium pump inlet filter series	Medium pump inlet filter series
Ambient		Metric	Imperial
11	Ambient temperature minimum	-20 °C	-4 °F
12	Ambient temperature maximum	50 °C	122 °F
13	Relative humidity minimum	0 %	0 %
14	Relative humidity maximum	100 %	100 %

	Gas	Metric	Imperial
15	Minimum flow / minute	5.0 Liter	1.3 Gallon
16	Maximum flow / minute	8.0 Liter	2.1 Gallon
17	Minimum flow / hour	300 Liter	79 Gallon
18	Maximum flow / hour	480 Liter	127 Gallon
19	Pressure minimum	50 kPa	7 PSI
20	Pressure maximum	300 kPa	44 PSI
21	Gas quality	No corrosive gasses: suitable for O <sub>2</sub> , air, CO <sub>2</sub> , N <sub>2</sub>	No corrosive gasses: suitable for O <sub>2</sub> , air, CO <sub>2</sub> , N <sub>2</sub>

22	Gas remark	The mentioned pressures are recommended pressures for bubble generation. The product itself can withstand pressures up to 500 kPa.	The mentioned pressures are recommended pressures for bubble generation. The product itself can withstand pressures up to 500 kPa.
----	------------	------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------

	Electrical	Metric	Imperial
23	Unit power consumption	No pump included with this product. Estimated power consumption 1500-2000 watts.	No pump included with this product. Estimated power consumption 1500-2000 watts.
24	Wetted parts	nylon based resins, PVC, EPDM rubber	nylon based resins, PVC, EPDM rubber
25	Pump model	Recommended: use of a low head centrifugal pump or pool pump	Recommended: use of a low head centrifugal pump or pool pump
26	Pump pressure setting	This product works well with most low head pumps. Head 10 to 15 meters. (Ask us for more details).	This product works well with most low head pumps. Head 10 to 15 meters. (Ask us for more details).
27	Control	Manual by pressure gauche	Manual by pressure gauche
	Connections	Metric	Imperial

Connections		Metric	Imperial
28	Water inlet	Rigid Rc 2" female coupling with thread	Rigid Rc 2" female coupling with thread
29	Water outlet	rigid Rc 1.5" female coupling with thread	rigid Rc 1.5" female coupling with thread
30	Gas inlet	10 mm standard quick fitting, 3/8 on request	10 mm standard quick fitting, 3/8 on request
Dimensions & weight		Metric	Imperial
31	Dim. (w) x (d) x (h)	644 x 200 x 1040 mm	25.4 x 7.9 x 40.9 inch
32	weight	26.5 Kg	58.4 lbs.
33	Shipping dim. (w)x(d)x(h)	67 x 37 x 107 cm	26 x 15 x 42 inch
34	Shipping weight	35 Kg	77 lbs.
Remarks			
35	Other remarks	 Easy to integrate with existing pool pumps	