



acniti LLC
1-2-9 Nyoidani
Minoh Osaka
562-0011
Japan



Ozone gas concentration sensor

Measure and control precisely ozone levels in gas measures from 0-60g/m³.
Measurement principle based on UV absorption or Polarographic with Polymeric.

Ozone gas concentration sensor

Measure accurately ozone gas levels

- ✓ High-Precision Ozone Detection
- ✓ Wide Measurement Range
- ✓ Real-Time Monitoring with Instant Readings
- ✓ Fast response time
- ✓ Compact and Portable Design
- ✓ Long Sensor Lifespan
- ✓ Versatile use

The Acniti Ozone Monitor is a state-of-the-art instrument designed for accurate, real-time measurements of ozone concentration in a variety of industries. Whether you're working in an industrial setting, greenhouse, laboratory, or water treatment facility, ozone plays a vital role in many processes, but it can be harmful even at low concentrations. Our Ozone Gas Sensors provide fast, accurate, and stable measurements to keep your environment safe and your systems under control.

Key features

High precision ozone detection

Our monitor uses advanced sensor technology to measure ozone concentrations with exceptional accuracy in real time. It detects even the smallest fluctuations in ozone levels, ensuring optimal performance in critical environments.

Wide measurement range

The Acniti Ozone Monitor has an impressive measurement range of 0-60 mg/L, making it suitable for a variety of applications. Whether you are monitoring ambient air quality or assessing high ozone concentrations in industrial environments, our device delivers reliable measurements across the spectrum.

Real-time monitoring with instant measurements

Get instantaneous data on ozone concentrations to make quick and informed decisions. This feature is critical in industrial environments where fast response times are essential for worker safety.

Compact and portable design

The lightweight and portable design of our monitor allows for easy deployment in both stationary and mobile applications. Take accurate measurements wherever you need them without sacrificing performance.

User-friendly interface

The Acniti Ozone Monitor features an intuitive, easy-to-read display that requires

minimal training to operate. This simplicity ensures that experienced professionals and newcomers alike can use the device effectively.

Durable construction

Built to withstand challenging environments, our monitor maintains high performance even when exposed to moisture, dust or extreme temperatures.

Applications

The Acniti Ozone Monitor excels in a variety of industries and applications:

- **Environmental monitoring:** Assess air quality and ozone pollution levels with precision
- **Industrial Safety:** Ensure worker safety and regulatory compliance in manufacturing, water treatment and chemical production facilities
- **Healthcare & Laboratories:** Monitor ozone levels in sterilization processes to maintain a safe environment for staff and patients
- **Agriculture:** Monitor ozone levels in greenhouses and warehouses for pest control and product preservation

Benefits of the Acniti Ozone Monitor

- **Accuracy and reliability:** Advanced sensors deliver reliable ozone concentration measurements in a variety of environments
- **Portability:** Conduct on-the-go assessments with our compact, lightweight design
- **Real-time data:** Receive instant ozone concentration readings for fast decision-making
- **User-friendly operation:** Intuitive interface requires minimal training, accessible to users of all experience levels
- **Versatility:** Suitable for a wide range of industries and applications

Conclusion

The Acniti Ozone Monitor stands out as a powerful, reliable and easy-to-use tool for accurate ozone measurement in a variety of environments. Its advanced sensor technology, portable design and real-time data capabilities make it an indispensable tool for professionals requiring accurate ozone concentration monitoring. Choose the Acniti Ozone Monitor for unmatched performance in environmental monitoring, industrial safety, healthcare, agriculture and more.

eg-550 series

	Beschreibung	Metrisch	Kaiserlich
1	Model name	EG-550 Series	EG-550 Series
2	Model number	EG-550	EG-550
	Flüssigkeit	Metrisch	Kaiserlich
3	Minimum flow / minute	0.1 Liter	0.0 Gallone
4	Maximum flow / minute	3.0 Liter	0.8 Gallone
5	Minimum flow / hour	3.0 Liter	0.8 Gallone
6	Maximum flow / hour	180 Liter	48 Gallone
	Elektrisch	Metrisch	Kaiserlich
7	Pump phase Ø voltage	AC 100V~220 V	AC 100V~220 V
	Abmessungen & Gewicht	Metrisch	Kaiserlich
8	Abm. (B) x (T) x (H)	220 x 105 x 150 mm	8.7 x 4.1 x 5.9 Zoll
9	weight	2.2 Kg	4.9 lbs.

eg-610 series

Beschreibung		Metrisch	Kaiserlich
1	Model name	EG-610 series	EG-610 series
2	Model number	EG-610	EG-610
Flüssigkeit		Metrisch	Kaiserlich
3	Minimum flow / minute	0.5 Liter	0.1 Gallone
4	Maximum flow / minute	20 Liter	5.3 Gallone
5	Minimum flow / hour	30 Liter	7.9 Gallone
6	Maximum flow / hour	1,200.0 Liter	317 Gallone
Elektrisch		Metrisch	Kaiserlich
7	Unit phase Ø voltage	AC100V~240V	AC100V~240V
8	Unit power consumption	25VA MAX	25VA MAX
Abmessungen & Gewicht		Metrisch	Kaiserlich
9	weight	1.6 Kg	3.5 lbs.