



acniti

LLC آکنی تی
۹-۲-۱ نی وای دانی
مین و اوزاکا
۰۰۱۱-۵۶۲۳
ژاپن

Underwater Oxidant Meter

The underwater oxidant meter is an advanced measuring instrument that detects oxidants in salt and brackish water without the need for reagents.

Underwater Oxidant Meter

Underwater Oxidant Meter

- Reagent-free measurement – No chemicals required ✓
- Automatic electrode cleaning ✓
- Quick measurements within 1 minute ✓
- Suitable for a variety of water conditions ✓
- No waste of water ✓
- Resistant to harsh environments ✓
- Easy integration into existing systems ✓
- Suitable for a variety of applications ✓
- (Wall mounting (and pipe mounting possible) ✓

?What does an Underwater Oxidant Meter do

The Underwater Oxidant Meter is an advanced measuring instrument that detects oxidants in salt and brackish water without the need for reagents. Thanks to potential pulse voltammetry with three electrodes, this meter provides fast and accurate measurements and remains reliable due to an innovative self-cleaning system.

An underwater Oxidant meter must not be confused with an ORP / Redox meter. See the [technology overview](#)

ORP / Redox Meter	Underwater Oxidant Meter	Technology overview
Electrochemical potential difference between two electrodes	Potential Pulse Voltammetry (PPV) with three electrodes	Measurement Principle
General oxidation-reduction potential (a combined effect of all redox species)	Direct measurement of oxidants (e.g., chlorine, ozone, H ₂ O ₂)	Target
No reagents, but indirect reading □	No reagents required □	Reagents Needed
Needs regular calibration for accuracy	Typically less frequent due to stable design	Calibration
Can be affected by high ionic strength and biofouling △	Yes, optimized for marine environments □	Designed for Salt / Brackish Water
Prone to fouling, requires regular maintenance □	Self-cleaning system □ helps avoid biofouling	Fouling Resistance
Limited submersion, not always pressure-rated △	Submersible and rugged □	Depth Rating
Moderate to slow, stabilizes over time	Fast, real-time detection ✂	Response Time

ORP / Redox Meter	Underwater Oxidant Meter	Technology overview
Low — gives a general redox state □ only	High — can distinguish □ between oxidants	Selectivity
Can drift, affected by □ contamination or coating on the probe	Excellent with pulse □ technology	Stability Over Time

?Why an Underwater Oxidant Meter

In various industrial and environmental applications, it is essential to monitor the presence of oxidants in water. The Underwater Oxidant Meter allows you to control water quality parameters, allowing you to efficiently

- Avoid unnecessary water consumption
- Works sustainably and is environmentally friendly without chemical reagents
- Saves costs on maintenance through automatic cleaning

Applications of the Underwater Oxidant Meter

The Underwater Oxidant Meter is used in various industries and applications. When you're looking for general water quality or are on a budget, consider an ORP meter.

Perfect applications for the Underwater Oxidant Meter

- **Water Treatment Plants** – Optimize Disinfection Processes
- **Aquaculture** in seawater
- **Precise** oxidant monitoring (e.g., ozone dosing)
- **Seawater sterilization in fisheries** – Ensure a clean environment for aquaculture
- **Wastewater treatment in factories** – Meet environmental standards
- **Swimming pools and spas** – Maintain safe water quality
- **Drinking water supply and sewage management** – Prevent contamination
- **Industrial processes** – Control oxidation-related chemical reactions

Specifications

Details	Feature
Oxidants in seawater and brackish water	Measurement Purpose
Three-electrode potential pulse voltammetry	Measurement Principle
Microelectrode system with self-cleaning beads	Measuring method
mg/L (Standard) – Optional: 1.0/3.0/5.0 mg/L	Measuring range
of full scale plus one digit $\pm 5\%$	Repeatability
(minute (90% response)	Response time

Details	Feature
Automatic compensation with a thermistor	Temperature compensation
pH range: 5.8–8.6 (variation within ± 0.5 pH)	
Conductivity: ≥ 10 mS/m (variation within ± 10 mS/m)	
Water temperature: $0 - 45^{\circ}\text{C}$ (no freezing)	Conditions
Ambient temperature: $-10 - 45^{\circ}\text{C}$	
(Humidity: $\leq 90\%$ RH (no condensation	
(Wall mounting (Optional: Tube mounting with U-bolt kit	Installation
mg/L 0.01	Resolution
(DC $4-20$ mA (Isolated, maximum load $500\ \Omega$	Signal Output
(Upper and lower limit alarms (1a each	Alarm outputs
Adjustable range:	
– $\pm 10\%$ of full scale	Control output
– $\pm 5\%$ of full scale	
– $\pm 2.5\%$ of full scale	
AC $100-240$ V ($\pm 10\%$ variation) $50/60$ Hz	Power supply
MPa 0.5	Pressure resistance
Stainless steel Tube Stand (1500 mm long) .1	
2. Attachment kit for tube (50 A)	
3. Connection box (sensor cable extension).	Optional accessories
4. Dedicated extension cable (available in 10 m lengths	

eoxi-۴۰

شرح	متری ک	امپری ال
۱ اسم مدل	EOXI-۴۰	EOXI-۴۰
۲ شماره مدل		EOXI-۴۰
مایع	متری ک	امپری ال
۳ موج و دیت و اندازه صافی		
گاز	متری ک	امپری ال
۴ کیفیت گاز		
۵ تذکر گاز		
اتصالات	متری ک	امپری ال
۶ ورودی آب		
۷ مجرای خروج آب		
۸ ورودی گاز		