



**acniti LLC**  
1-2-9 Nyoidani  
Minoh Osaka  
562-0011  
Japan



## underwater oxidant meter

Discover the advanced Underwater Oxidant Meter designed for fast, accurate measurement of oxidants like chlorine and ozone in salt or brackish water—without the need for reagents. Its innovative self-cleaning and three-electrode technology ensure highly reliable performance, even in challenging marine environments. Learn how this rugged, easy-to-maintain instrument sets a new standard for water quality monitoring in industrial, environmental, and research applications.

# underwater oxidant meter

## underwater oxidant meter

**Deprecated:** `mb_convert_encoding()`: Handling HTML entities via `mbstring` is deprecated; use `htmlspecialchars`, `htmlentities`, or `mb_encode_numericentity/mb_decode_numericentity` instead in </var/www/cpw/site/modules/ProductPdf/ProductPdf.module.php> on line **762**








- ✓ Reagent-free measurement - No chemicals required
- ✓ Automatic electrode cleaning
- ✓ Quick measurements within 1 minute
- ✓ Suitable for a variety of water conditions
- ✓ No waste of water
- ✓ Resistant to harsh environments
- ✓ Easy integration into existing systems
- ✓ Suitable for a variety of applications
- ✓ Wall mounting (and pipe mounting possible)

## what does an underwater oxidant meter do?

The Underwater Oxidant Meter is an advanced measuring instrument that detects oxidants in salt and brackish water without the need for reagents. Thanks to potential pulse voltammetry with three electrodes, this meter provides fast and accurate measurements and remains reliable due to an innovative self-cleaning system.

An underwater Oxidant meter must not be confused with an ORP / Redox meter. See the technology overview:

Technology overview	Underwater Oxidant Meter	ORP / Redox Meter
Measurement Principle	Potential Pulse Voltammetry (PPV) with three electrodes	Electrochemical potential difference between two electrodes
Target	Direct measurement of oxidants (e.g., chlorine, ozone, H <sub>2</sub> O <sub>2</sub> )	General oxidation-reduction potential (a combined effect of all redox species)
Reagents Needed	■ No reagents required	■ No reagents, but indirect reading
Calibration	Typically less frequent due to stable design	Needs regular calibration for accuracy
Designed for Salt / Brackish Water	■ Yes, optimized for marine environments	▲ Can be affected by high ionic strength and biofouling
Fouling Resistance	■ Self-cleaning system helps avoid biofouling	■ Prone to fouling, requires regular maintenance

Technology overview	Underwater Oxidant Meter	ORP / Redox Meter
Depth Rating	 Submersible and rugged	 Limited submersion, not always pressure-rated
Response Time	 Fast, real-time detection	Moderate to slow, stabilizes over time
Selectivity	 High — can distinguish between oxidants	 Low — gives a general redox state only
Stability Over Time	 Excellent with pulse technology	 Can drift, affected by contamination or coating on the probe

## why an underwater oxidant meter?

In various industrial and environmental applications, it is essential to monitor the presence of oxidants in water. The Underwater Oxidant Meter allows you to control water quality parameters, allowing you to efficiently:

- Avoid unnecessary water consumption
- Works sustainably and is environmentally friendly without chemical reagents
- Saves costs on maintenance through automatic cleaning

## applications of the underwater oxidant meter.

The Underwater Oxidant Meter is used in various industries and applications. When you're looking for general water quality or are on a budget, consider an ORP meter. Perfect applications for the Underwater Oxidant Meter:

- **Water Treatment Plants** - Optimize Disinfection Processes.
- **Aquaculture** in seawater
- **Precise** oxidant monitoring (e.g., ozone dosing)
- **Seawater sterilization in fisheries** - Ensure a clean environment for aquaculture
- **Wastewater treatment in factories** - Meet environmental standards
- **Swimming pools and spas** - Maintain safe water quality
- **Drinking water supply and sewage management** - Prevent contamination
- **Industrial processes** - Control oxidation-related chemical reactions

## specifications

Feature	Details
Measurement Purpose	Oxidants in seawater and brackish water
Measurement Principle	Three-electrode potential pulse voltammetry
Measuring method	Microelectrode system with self-cleaning beads
Measuring range	0-2.00 mg/L (Standard) - Optional: 1.00/3.00/5.00 mg/L
Repeatability	±5% of full scale plus one digit
Response time	1 minute (90% response)
Temperature compensation	Automatic compensation with a thermistor

Feature	Details
Conditions	<b>pH range:</b> 5.8-8.6 (variation within $\pm 0.5$ pH) <b>Conductivity:</b> $\geq 10$ mS/m (variation within $\pm 10$ mS/m) <b>Water temperature:</b> 0 - 45°C (no freezing) <b>Ambient temperature:</b> -10 - 45°C <b>Humidity:</b> $\leq 90\%$ RH (no condensation)
Installation	Wall mounting (Optional: Tube mounting with U-bolt kit)
Resolution	0.01 mg/L
Signal Output	DC 4- 20mA (Isolated, maximum load 500 $\Omega$ )
Alarm outputs	Upper and lower limit alarms (1a each) Adjustable range: <ul style="list-style-type: none"><li>- <math>\pm 10\%</math> of full scale</li><li>- <math>\pm 5\%</math> of full scale</li><li>- <math>\pm 2.5\%</math> of full scale</li></ul>
Control output	
Power supply	AC 100-240V ( $\pm 10\%$ variation) 50/60Hz
Pressure resistance	0.5 MPa
Optional accessories	<ol style="list-style-type: none"><li>1. Stainless steel Tube Stand (1500 mm long)</li><li>2. Attachment kit for tube (50A)</li><li>3. Connection box (sensor cable extension).</li><li>4. Dedicated extension cable (available in 10 m lengths).</li></ol>

# eoxi-40

Description		Metric	Imperial
1	Model name	EOXI-40	EOXI-40
2	Model number	EOXI-40	EOXI-40
Liquid		Metric	Imperial
3	Strainer availability and size		
Gas		Metric	Imperial
4	Gas quality		
5	Gas remark		
Connections		Metric	Imperial
6	Water inlet		
7	Water outlet		
8	Gas inlet		