



acniti LLC
1-2-9 Nyoidani
Minoh Osaka
562-0011
Japan



residual chlorine meter: reagent-free monitoring | acniti

This reagent-free residual chlorine meter uses 3-electrode pulse voltammetry for continuous, maintenance-free monitoring of free chlorine in drinking water and industrial systems. Available in two models - an economical option with 0.1 mg/L resolution and a high-precision option with 0.01 mg/L resolution - for water treatment plants, distribution networks, hospitals, and industrial facilities.

residual chlorine meter: reagent-free monitoring | acniti

reagent-free residual chlorine meter for water treatment

- ✓ No need for chemicals
- ✓ Measures only free residual
- ✓ Automatic sensor cleaning
- ✓ Wide measuring range
- ✓ Excellent repeatability
- ✓ Fast response
- ✓ Robust installation options

The ECLG-35 Residual Chlorine Meter is a high-precision, reagent-free sensor designed for continuous monitoring of free residual chlorine in drinking water and industrial water systems. Utilizing a 3-electrode pulse voltammetry method, the ECLG-35 provides accurate and stable measurements without the need for chemical reagents.

why choose the eclg-35?

The sensor features an advanced automatic cleaning system, combining bead flow and electrolytic cleaning to maintain consistent sensitivity and minimize drift over time. With a measuring range of 0.00-3.00 mg/L, high repeatability ($\pm 2\%$ FS), and a fast response time ($T_{90} \leq 1$ minute), the ECLG-35 ensures reliable chlorine control under varying water conditions.

This unit is equipped with automatic temperature compensation and a built-in thermistor, ensuring stable performance across a wide pH and conductivity range. Installation is flexible: wall-mounting is standard, or optional pipe-mounting on $\varnothing 50$ mm tubing.

priority to safe, clean water

With reagent-free operation, built-in cleaning, and excellent measurement stability, the ECLG-35 ensures accurate, long-term chlorine control, eliminating the need for routine maintenance or consumables—ideal for utilities and facilities where a safe and clean water supply is a top priority.

The Residual Chlorine Meter ECLG-35 is ideal for use in water treatment plants, distribution networks, buildings, hospitals, hotels, and the food or pharmaceutical industries. The ECLG-35 provides peace of mind in water safety and regulatory compliance. All while operating without

consumables or complex maintenance procedures.

typical applications

- Drinking water production and distribution
- On-site water supply (hospitals, schools, hotels)
- Storage tanks and reservoirs
- Industrial water disinfection (food, pharma)
- Real-time quality monitoring without consumables

technical specifications

Parameter	Details
Measurement principle	3-electrode pulse voltammetry
Measuring range	0.00 – 3.00 mg/L (free residual chlorine)
Repeatability	±2 % FS + 1 digit (3 mg/L range)
Linearity	±5 % FS + 1 digit
Zero/Span drift	≤ ±1 % FS (zero), ≤ ±10 % FS/month (span)
Response time (T90)	≤ 1 minute
Temperature compensation	Automatic (built-in thermistor)
Power supply	100–240 V AC, 50/60 Hz (~20 VA)
Sample water conditions	pH: 5.8–8.6, Conductivity: 5–100 mS/m, Temp: 0–40 °C
Installation method	Wall mount (standard), optional 50 mm pipe mount
Operating temperature	-10 – 45 °C, RH ≤ 90 % (non-condensing)
Storage temperature	-20 – 60 °C

If you need a durable, low-maintenance chlorine meter that delivers long-term accuracy and efficiency, the ECLG-35 is the wise choice.

ecli-35: residual chlorine meter 0-3 mg/l 100-240v I acniti

General

- | | | |
|---|--------------|--|
| 1 | Model name | Reagent-Free Residual Chlorine Meter for Water Treatment |
| 2 | Model number | sensor_chlorine_li_water_concentration |

Liquid

Metric

Imperial

- 3 Strainer availability and size

Gas

Metric

Imperial

- 4 Gas quality

- 5 Gas remark

Connections

- 6 Water inlet

- 7 Water outlet

- 8 Gas inlet

Dimensions & weight

Metric

Imperial

- | | | |
|---|---------|-----------|
| 9 | HS code | 9027-9090 |
|---|---------|-----------|

Remarks

- | | | |
|----|---------------|---|
| 10 | Other remarks | <p>The main distinction between the ECLG-35 and ECLI-35 lies in their display resolution and measurement precision</p> <ul style="list-style-type: none"> ✓ Measurement Range: 0~3mg/L ✓ Display Resolution: Lower precision with 0.1mg/L minimum display increment (displays to tenths) ✓ The ECLI-35 is more economical than the ECGI-35 |
|----|---------------|---|

ecdg-35: residual chlorine meter 0-3 mg/l 100-240v I acniti

General

- | | | |
|---|--------------|--|
| 1 | Model name | Reagent-Free Residual Chlorine Meter for Water Treatment |
| 2 | Model number | sensor_chlorine_lg_concentration |

Liquid

Metric

Imperial

- | | | | |
|---|--------------------------------|--|--|
| 3 | Strainer availability and size | | |
|---|--------------------------------|--|--|

Gas

Metric

Imperial

- | | | | |
|---|-------------|--|--|
| 4 | Gas quality | | |
| 5 | Gas remark | | |

Connections

- | | | | |
|---|--------------|--|--|
| 6 | Water inlet | | |
| 7 | Water outlet | | |
| 8 | Gas inlet | | |

Dimensions & weight

Metric

Imperial

- | | | | |
|---|---------|-----------|--|
| 9 | HS code | 9027.9090 | |
|---|---------|-----------|--|

Remarks

- | | | |
|----|---------------|--|
| 10 | Other remarks | <ul style="list-style-type: none">✓ The main distinction between the ECLG-35 and ECLI-35 lies in their display resolution and measurement precision✓ Measurement Range: 0.00~3.00mg/L✓ Display Resolution: Higher precision with 0.01mg/L increments (displays to hundredths)✓ The ECGI-35 is more expensive than the ECLI-35 |
|----|---------------|--|